

## AXIS Q3615-VE Network Camera

Outstanding image quality with easy installation

Thanks to its 1/1.9" sensor and high-performance image processing, AXIS Q3615-VE supports Lightfinder and WDR - Forensic Capture with optimal image quality in difficult light conditions. It provides HDTV 1080p video at 30 fps with WDR, or up to 60 fps with WDR disabled. AXIS Q3615-VE offers a unique remote pan/tilt/roll/zoom (PTRZ) solution, easy conduit connection and cable management for minimized installation time. The PTRZ capability is also useful if the camera needs to be redirected. Robust and reliable, AXIS Q3615-VE is designed for harsh environments. Electronic image stabilization delivers steady images even during vibrations.

- > [Exceptional video quality with 1/1.9" sensor](#)
- > [Lightfinder and WDR - Forensic Capture](#)
- > [HDTV 1080p up to 60 fps](#)
- > [Unique remote PTRZ capability for efficient installation](#)
- > [Axis Zipstream technology](#)



# AXIS Q3615-VE Network Camera

<b>Camera</b>		
<b>Image sensor</b>	Progressive scan RGB CMOS 1/1.9"	Video recording to edge storage, pre- and post-alarm video buffering, zoom or digital PTZ preset, overlay text, send SNMP trap
<b>Lens</b>	Varifocal, 4.1–9 mm, F1.6 Horizontal field of view: 100°–46° Vertical field of view: 60°–29° Remote focus and zoom, P-Iris control, IR corrected	
<b>Day and night</b>	Automatically removable infrared-cut filter	
<b>Minimum illumination</b>	HDTV 1080p 25/30 fps with WDR - forensic capture and Lightfinder: Color: 0.1 lux at 50 IRE, F1.6; B/W: 0.02 lux at 50 IRE, F1.6 HDTV 1080p 50/60 fps: Color: 0.2 lux at 50 IRE, F1.6; B/W: 0.03 lux at 50 IRE, F1.6	
<b>Shutter time</b>	1/52500 s to 2 s	
<b>Camera angle adjustment</b>	Pan 370° Tilt +/- 81° Roll +/- 110°	
<b>Video</b>		
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	
<b>Resolution</b>	1920x1200 to 160x90	
<b>Frame rate</b>	HDTV 1080p (1920x1080) with WDR: 25/30 fps with power line frequency 50/60 Hz HDTV 1080p (1920x1080) without WDR: 50/60 fps with power line frequency 50/60 Hz WUXGA (1920x1200) without WDR: 25/30 fps with power line frequency 50/60 Hz	
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	
<b>Multi-view streaming</b>	2 individually cropped out view areas	
<b>Image settings</b>	Compression, color, brightness, sharpness, contrast, white balance, exposure control, exposure zone, noise reduction, fine tuning of behavior at low light, rotation: 0°, 90°, 180°, 270° including Corridor Format, text and image overlay, privacy mask, mirroring of images, electronic image stabilization, barrel distortion correction WDR - forensic capture: Up to 120 dB depending on scene	
<b>Pan/Tilt/Zoom</b>	2.2x optical zoom and 2x digital zoom Digital PTZ Optical zoom and digital PTZ preset positions	
<b>Network</b>		
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log, Centralized Certificate Management	
<b>Supported protocols</b>	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP	
<b>System integration</b>		
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://www.axis.com">www.axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF <sup>®</sup> Profile S and ONVIF <sup>®</sup> Profile G, specification at <a href="http://onvif.org">onvif.org</a>	
<b>Analytics</b>	<b>Included</b> AXIS Video Motion Detection, active tampering alarm <b>Supported</b> AXIS Perimeter Defender, AXIS Digital Autotracking Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a>	
<b>Event triggers</b>	Analytics, Edge storage events, Shock detection	
<b>Event actions</b>	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP	
<b>Data streaming</b>	Event data	
<b>Built-in installation aids</b>	Pan/tilt/roll: designed to withstand at least 200 full cycles, autoroll, remote zoom, remote focus, pixel counter	
<b>General</b>		
<b>Casing</b>	IP66-, IP67-, IP6K9K- and NEMA 4X-rated, IK10 impact-resistant casing with polycarbonate dome, aluminum base and dehumidifying membrane Color: White NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.	
<b>Sustainability</b>	PVC free	
<b>Memory</b>	512 MB RAM, 256 MB Flash	
<b>Power</b>	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.5 W, max 10.4 W	
<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX PoE	
<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a>	
<b>Operating conditions</b>	-40 °C to 60 °C (-40 °F to 140 °F) Humidity 10–100% RH (condensing)	
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)	
<b>Approvals</b>	<b>EMC</b> EN 55022 Class B, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN32 Class B, KN35 <b>Safety</b> IEC/EN/UL 60950-22 <b>Environment</b> IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66/67, ISO 20653 IP6K9K, NEMA 250 Type 4X, IEC/EN 62262 IK10	
<b>Dimensions</b>	Depth: 166 mm (6 9/16 in) Depth with weathershield: 224 mm (8 13/16 in) ø 198 mm (7 13/16 in)	
<b>Weight</b>	2.3 kg (5.1 lb) with weather shield	
<b>Included accessories</b>	AXIS Connector Guard A, Safety hook wire, Installation Guide, Windows decoder 1-user license, Resistor <sup>®</sup> L-key, Weathershield, Mounting bracket, Drill template, Cable gasket, Axis U-shape conduit adapter	
<b>Optional accessories</b>	AXIS T94V01L Recessed Mount, AXIS T94V01D Pendant Kit, AXIS T98A17-VE Cabinets, Axis Pole Mounts, Axis Ceiling Mounts, Axis Wall Mounts, AXIS T90B Illuminators, AXIS ACI Conduit Adapter 3/4" NPS, AXIS Q36-VE Smoked Dome, AXIS Surveillance microSDXC <sup>™</sup> Card For more accessories, see <a href="http://www.axis.com">www.axis.com</a>	
<b>Video management software</b>	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/vms">www.axis.com/vms</a>	
<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	
<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>	
a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<a href="http://www.openssl.org">www.openssl.org</a>), and cryptographic software written by Eric Young (<a href="mailto:ey@cryptsoft.com">ey@cryptsoft.com</a>).</i>		
<b>Environmental responsibility:</b> <a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a>		