

## AXIS A8004-VE Network Video Door Station

### Reliable audiovisual entry control

The weather and vandal-resistant AXIS A8004-VE is an open, non-proprietary, IP-based network video door station for two-way communication, video identification, and remote entry control. A perfect complement to any surveillance installation, it provides an easy way to add communication and entry control to surveillance systems. IP standards and an open interface enable integration in both small and enterprise systems, and with third-party video management software. AXIS A8004-VE offers excellent low-light performance with WDR, reliable 24/7 identification, and clear two-way speech thanks to echo cancellation and noise reduction. It has multiple inputs and outputs for remote control of door locks and other equipment.

- > **High-quality audio and video**
- > **Easy to install, PoE+**
- > **Open interface**
- > **IP phone integration and SIP support**
- > **Remote entry control**

**SIP**

# AXIS A8004-VE Network Video Door Station

<b>Camera</b>		<b>Event actions</b>	Make call: SIP, API File upload: FTP, HTTP, network share and email Notification: email, HTTP and TCP Video and audio recording to edge storage, Pre- and post-alarm video buffering, External output activation, Play audio clip, Overlay text, PTZ control, Status LED, WDR mode
<b>Image sensor</b>	1/3" Progressive scan RGB CMOS	<b>Data streaming</b>	Event data
<b>Lens</b>	M12 mount, F2.8, Fixed iris, Megapixel resolution, 2.8 mm, 97° view <sup>a</sup>	<b>Built-in installation aids</b>	Pixel counter
<b>Light sensitivity</b>	0.4 - 100000 lux, F2.8, 0 lux with illumination LED on	<b>General</b>	
<b>Shutter time</b>	Dynamic capture, 1/192 s to 1/37 s (50 Hz), 1/231 s to 1/44 s (60 Hz)	<b>Casing</b>	Brushed stainless steel front plate. Aluminum body: IP66-rated, NEMA 4x-rated, IK08 impact-resistant
<b>Video</b>		<b>Sustainability</b>	PVC free
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC), Baseline Profile, Main Profile, Motion JPEG	<b>Memory</b>	256 MB RAM, 128 MB Flash
<b>Resolutions</b>	1280x960 (1.3 MP) to 160x90	<b>Power</b>	Power In: Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3, 10-28 V DC min. 25 W; Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4; Power out <sup>c</sup> : 2x12 V DC, max. depending on Power In to AXIS A8004-VE; PoE Class 3: max. out 160 mA at 12 V DC Relay pin, I/O 50 mA at 12 V DC IO pin; PoE+ Class 4: max. out 750 mA at 12 V DC Relay pin, I/O 200 mA at 12 V DC IO pin; DC in: max. out 750 mA at 12 V DC Relay pin, I/O 200 mA at 12 V DC IO pin; Relays: Locks/etc sourced from AXIS A8004-VE: Maximum current is stated in Power out section. Locks/etc sourced externally: Maximum voltage/current is 0.7A at 30 V
<b>Frame rate</b>	HDTV 720p (1280x720), 25/30 fps (50/60 Hz)	<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX, PoE, DC Power, 4 Inputs/outputs, 2 relays, Line out
<b>Video streaming</b>	Multiple individually configurable streams, H.264, Motion JPEG, Controllable frame rate and bandwidth, VBR/CBR H.264	<b>Storage</b>	microSD/microSDHC/microSDXC slot (card not included). Support for recording to network share (network-attached storage or file server)
<b>Image settings</b>	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Fine-tuning of behavior at low light, WDR - Dynamic Capture, Text and image overlay, Mirroring of images, Privacy mask	<b>Operating conditions</b>	-25 °C to 50 °C (-13 °F to 122 °F) Humidity 10-100% RH (condensing)
<b>Pan/Tilt/Zoom</b>	Digital PTZ	<b>Dimensions</b>	Wall mount: 140 x 260 x 55.5 mm (5.5 x 10 x 2.2 in); Recessed wall mount: 140 x 260 x 21 mm (5.5 x 10 x 0.8 in)
<b>Audio</b>		<b>Weight</b>	Main unit: 1.5 kg (3.3 lb); Wall mount frame: 0.370 kg (0.82 lb); Total weight: 1.87 kg (4.12 lb)
<b>Audio streaming</b>	Two-way, Full duplex	<b>Approvals</b>	EN 55022 Class A, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, C-tick AS/NZS CISPR22 Class A, IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, EN 50581, IEC 60529 IP66/IP67, NEMA 250 Type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC/EN 62262 IK08
<b>Audio compression</b>	AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8kHz, Configurable bit rate	<b>Included accessories</b>	Installation Guide, Wall mount frame, Resistorx T20 L-key, Resistorx T10 L-key, Plug connectors (power, I/O, line-out, relay), Cable gasket, AXIS Connector guard A, AVHS Authentication key
<b>Audio output</b>	85 dB (at 0.5 m)	<b>Mounting option</b>	Wall mount: Frame included. Recessed mount: Use AXIS A8004 Junction Box or RACO 942 3-Gang 2-1/2" DP
<b>Audio input/output</b>	Line output, Built-in microphone, Built-in speaker	<b>Optional accessories</b>	AXIS A8004 Junction box, AXIS A9801 Security Relay, Safety relay
<b>Echo cancellation</b>	Yes	<b>Video management software</b>	Video management software from Axis' Application Development Partners (not included). For more information, see <a href="http://www.axis.com/products/video/software">www.axis.com/products/video/software</a>
<b>Noise reduction</b>	Yes	<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>
<b>Network</b>			
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>b</sup> encryption, IEEE 802.1X <sup>9</sup> network access control, Digest authentication, User access log		
<b>Supported protocols</b>	IPv4/IPv6, HTTP, HTTPS <sup>b</sup> , SSL/TLS <sup>b</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SIP		
<b>System integration</b>			
<b>Application Programming Interface</b>	Open API for software integration including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://www.axis.com">www.axis.com</a> , AXIS Video Hosting System (AVHS) with One-click Connection, ONVIF Profile S; specification available at <a href="http://www.onvif.org">www.onvif.org</a>		
<b>Software</b>	Third-party video management software and mobile applications. See <a href="http://www.axis.com">www.axis.com</a> for combatibility		
<b>VoIP</b>	SIP support for integration with VoIP, Peer-to-peer or integrated with SIP/PBX. Tested with various SIP softwares such as Cisco, Bria and Grandstream. Tested with various PBX softwares such as Cisco, Avaya and Asterisk.		
<b>Analytics</b>	Video motion detection, Active tampering alarm, Audio detection, AXIS Camera Application Platform enabling installation of additional applications, External input, Edge storage events, Shock detection		
<b>Event triggers</b>	Call: DTMF, State, State changes Detectors: Video motion detection, Audio detection, Live stream accessed, Shock detection, Tampering Hardware: Casing open, Network Input signal: Digital input port, Manuel trigger, Virtual input PTZ: Moving, Preset reached Storage: Disruption, Recording System: System ready Time: Use schedule		

- a. Horizontal angle of view  
b. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([www.openssl.org](http://www.openssl.org)), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).  
c. Support for two locks (max. total 750 mA) when powered with DC/PoE Class 4. For higher power requirements connect external power (max. 30V DC 0.7A).

#### Environmental responsibility:

[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)