

AXIS P3227-LV Network Camera

Streamlined 5 MP fixed dome for any light conditions

AXIS P3227-LV is a streamlined 5 MP fixed dome that features a varifocal lens with remote zoom and focus, which facilitates installation and eliminates the need for hands-on fine tuning. Equipped with Forensic WDR to handle scenes with strong variations in light, Lightfinder technology, as well as built-in IR illumination with OptimizedIR, this versatile camera provides exceptional video quality in any light conditions. It supports Axis Zipstream technology that significantly reduces bandwidth and storage requirements.

- > **5 MP resolution in full frame rate**
- > **Forensic WDR and Lightfinder**
- > **OptimizedIR illumination**
- > **Remote zoom and focus**
- > **Zipstream for reduced bandwidth and storage needs**



AXIS P3227-LV Network Camera

Camera		Overlay text, IR illumination on/off
Image sensor	Progressive scan RGB CMOS 1/2.5"	Data streaming Event data
Lens	Varifocal, 3.5–10 mm, F1.7 Horizontal field of view: 100°–38° Vertical field of view: 51°–22° Remote zoom and focus, P-Iris control, IR corrected	Built-in installation aids Remote zoom, remote focus, pixel counter
Day and night	Automatically removable infrared-cut filter	General
Minimum illumination	Color: 0.18 lux at 50 IRE, F1.7 B/W: 0.04 lux F1.7 at 50 IRE, 0 lux with IR illumination on	Casing IP52-rated, IK08 impact-resistant, polycarbonate casing with hard-coated dome and dehumidifying membrane Encapsulated electronics and captive screws Color: white NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.
Shutter time	1/62500 s to 2 s	Mounting Mounting bracket with holes for junction boxes (double-gang, single-gang, and 4" octagon) and for wall or ceiling mount ¼"-20 UNC tripod screw thread
Camera angle adjustment	Pan ±180°, tilt -40 to +75°, rotation ±95°	Sustainability PVC free
Video		Memory 1 GB RAM, 512 MB Flash
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Power Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, max 11.5 W, typical 8.4 W
Resolution	3072x1728 to 160x90	Connectors RJ45 10BASE-T/100BASE-TX PoE Audio and I/O connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology
Frame rate	25/30 fps with power line frequency 50/60 Hz	IR illumination Optimized IR with power-efficient, long-life 850 nm IR LEDs. Range of reach 30 m (100 ft) or more depending on the scene
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264	Storage Support for microSD/microSDHC/microSDXC card SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Multi-view streaming	8 individually cropped out view areas.	Operating conditions 0 °C to 50 °C (32 °F to 122 °F) Humidity 10 to 85% RH (non-condensing)
Pan/Tilt/Zoom	Digital PTZ, Preset positions	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Image settings	Compression, Color, Brightness, Sharpness, Contrast, Local contrast, White balance, Exposure control (including automatic gain control), Exposure zones, Fine tuning of behavior at different light levels, Forensic WDR: up to 120 dB depending on scene, Text and image overlay, Mirroring of images, Privacy masks Rotation: 0°, 90°, 180°, 270°, including Corridor Format	Approvals EMC EN 55032 Class B, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A and B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN32 Class B, KN35 Safety IEC/EN/UL 60950-1, IEC/EN 62471, IS 13252 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14 IEC 60068-2-6 (vibration), IEC 60068-2-27 (shock), IEC 60068-2-30, IEC 60068-2-78, IEC/EN 60529 IP52, IEC/EN 62262 IK08 Network NIST SP500-267
Audio		Dimensions Height: 101 mm (4 in) ø 149 mm (5 7/8 in)
Audio input/output	Two-way audio connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology	Weight 550 g (1.2 lb)
Network		Included accessories Installation guide, Windows decoder 1-user license, mounting bracket, cable gasket, Resistorx®T20 L-key, drill template, connector guard
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware	Optional accessories AXIS T6101 Audio and I/O Interface AXIS T6112 Audio and I/O Interface AXIS ACI Conduit Bracket B AXIS ACI Conduit Adapters AXIS T94K01L Recessed Mount Kit AXIS T94S01L Recessed Mount Kit AXIS T94K01D Pendant Kit AXIS Skin Cover C, Black AXIS MOUNTS AXIS P32-V Smoked Dome A
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SIP, SOCKS, SSH, LLDP	Video management software AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on axis.com/vms
System integration		Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF® Profile G, ONVIF® Profile S, and ONVIF® Profile T specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX	Warranty Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty
Analytics	Included AXIS Video Motion Detection, active tampering alarm Supported AXIS Digital Autotracking, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, AXIS Perimeter Defender, AXIS Demographic Identifier Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	
Event triggers	Analytics, edge storage events, virtual inputs through API	
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap	

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).*

Environmental responsibility:
axis.com/environmental-responsibility