

Streamvault SVW-300E

Security workstation

The Genetec Streamvault™ SVW-300E workstation is a turnkey solution designed for small and medium-sized security system monitoring. With support for multiple displays and Security Center pre-installed, it helps operators keep a watchful eye on your installations.

Guaranteed performance

up to
> 8
monitors

up to
> 42
full HD
streams



Key features

Turnkey workstation with Genetec™ Security Center pre-installed

Connect up to 8 monitors

Display up to 42 full high-resolution video streams

5-year hardware warranty with next business-day on-site support and hard drive retention

Benefits



Compact design – With its small form-factor, the SVW-300E workstation fits seamlessly into your environment.



Smooth performance – The SVW-300E workstation takes advantage of the Security Center GPU-accelerated decoding feature to deliver fluid playback of live and recorded high definition video.



Turnkey deployment – All Streamvault solutions come with Security Center pre-loaded and ready to go, so you can get your system up and running faster.

Applications

Corporate offices

Whether you are looking to add a security workstation to your office or provide live viewing capabilities to reception staff, the SVW-300E workstation is a cost-effective solution for corporate environments.

Retail

Display live camera feeds in public areas using a discreet workstation that can be easily be stored behind the counter, and enhance safety and security.

Technical specifications

OS

Windows 10 LTSC

Processor

SFF/T1: Intel® Core™ i7-9700 4.60 GHz

T3: Intel® Core™ i7-9700k 4.70 GHz

Graphics card

Consult the catalog for models

Display

Consult the catalog for models

Memory

Single GPU: 16 GB Dual GPU: 32 GB

Ethernet

1GbE RJ45 Ports

Processor Passmark™

SFF: 15,248

T1: 15,248

T3: 15,972

OS drive

128 GB SSD

Peripherals

SFF: 2x USB 3.1 / 2x USB 2.0

T1: 4x USB 3.1 / 4x USB 2.0

T3: 4x USB 3.0 / 2x USB 2.0

T1/T3: 2x 3.5 mm audio out

Mechanical and environmental

Power supply

SFF: 200W (100-240 VAC)

T1: 260W (100-240 VAC)

T3: 460W (100-240 VAC)

Operating temperature

SFF: 41°F to 95°F (5°C to 35°C)

T1: 50°F to 95°F (10°C to 35°C)

T3: 50°F to 95°F (10°C to 35°C)

Operating humidity

SFF/T1: 20 - 80% (non-condensing)

T3: 5 - 90% (non-condensing)

Dimensions (W x D x H)

SFF: 3.7" x 11.5" x 11.4"

(97mm x 292mm x 290mm)

T1: 6.1" x 10.8" x 13.8"

(154mm x 274mm x 350mm)

T3: 6.89" x 17.12" x 14.17"

(175mm x 434.8mm x 359.9mm)

Max Weight

SFF: 11.42 lbs (5.14 kg)

T1: 17.49 lbs (7.93 kg)

T3: 20.06 lbs (9.1 kg)

Certifications

IEC 60950-1, European Norm EN 60950-1,

CISPR 22/CISPR 24, EN55022/55024

Warranty

Hardware

5-year warranty with next business day on-site service and Keep your own

Hard Drive
