

AXIS P7316 Video Encoder

Full-featured, 16-channel video encoder

AXIS P7316 is a full-featured, 16-channel video encoder that adds IP benefits to any analog camera system. It supports standard and HD analog cameras up to 4K resolution as well as PTZ control over RS485. This rack-mounted encoder features support for two-way audio and intelligent analytics such as motion detection and active tampering alarm. An SFP slot enables long-distance fiber-optic connection and network redundancy. AXIS P7316 includes Zipstream with support for H.264/H.265 to drastically reduce bandwidth and storage requirements. Furthermore, it offers built-in cybersecurity features such as signed firmware and secure boot.

- > [Support for HD analog cameras up to 4K](#)
- > [PTZ control](#)
- > [2-way audio and configurable I/O](#)
- > [Zipstream with support for H.264/H.265](#)
- > [Signed firmware and secure boot](#)



AXIS P7316 Video Encoder

System on chip (SoC)		Data streaming	Event data
Model	4x ARTPEC-7	Analytics	
Memory	4x 1024 MB RAM, 512 MB Flash Battery backed-up real-time clock	Applications	Included AXIS Video Motion Detection, active tampering alarm Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
Video		General	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High profiles H.265 (MPEG-H Part 2/HEVC) Main profile Motion JPEG	Casing	Metal casing 1U stand alone, rackmount or wallmount Color: NCS S 5502-B
Resolution	176x144/176x120 (PAL/NTSC) to 720x576/720x480 (PAL/NTSC) High definition TVI, high definition CVI and high definition analog HD (1280x720 and 1920x1080) 4x one channel 4K (3840x2160)	Sustainability	PVC free
Frame rate	25/30 fps in all resolutions up to 1080p Up to 30 fps in quad view in full resolution 1080p 4x one channel 4K up to 15 fps	Power	max 32 W
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Quad view	Connectors	16 pcs analog video BNC inputs 8 pcs 3.5 mm mic/line in 4 pcs 3.5 mm audio line out 1 pc 1000 BASE-TX Ethernet (RJ45) 1 pc auxiliary ethernet (RJ45) 1 pc Gbps SFP slot 4 pcs terminal block for up to 4 configurable external input/output 4 pcs terminal block for RS485/RS422 serial communication (full duplex) 1 pc DC input terminal block
Image settings	Rotation: 0°, 90°, 180°, 270°, de-interlace filter, Compression, color, brightness, contrast, aspect ratio correction, mirroring of images, text and image overlay, polygon privacy mask, video termination, sharpness, noise reduction	Storage	Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Audio		Operating conditions	0 °C to 50 °C (32 °F to 122 °F) Humidity 10–85% RH (non-condensing)
Audio streaming	Two-way, full duplex	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Audio encoding	24bit LPCM, AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, Configurable bit rate	Approvals	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835 Safety IEC/EN/UL 62368-1 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 Network NIST SP500-267
Audio input/output	8 analog or digital external microphone input or line input, and 4 line output	Dimensions	44 x 145 x 440 mm (1.7 x 5.7 x 17.3 in)
Network		Weight	2100 g (4.6 lb)
IP address	Four IP address, one per four channels	Included accessories	Installation guide, Windows® decoder 1-user license, mains power supply, mounting kit (incl 2 mount brackets and 4 rubber feet) and connector kit (8 pcs 2-pin RS485/RS422 plugs, 4 pcs 6-pin I/O plugs)
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a , network access control, digest authentication, user access log, multi-level user, brute force delay protection, signed firmware, secure boot, Axis Edge Vault with Axis device ID	Optional accessories	For accessories, see axis.com
Supported protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS ^a , HTTP/2, TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS [™] , NTP, RTSP, RTP, SRTP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)	Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
System integration		Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org	Warranty	5-year warranty, see axis.com/warranty
Event conditions	Device status: IP address removed, network lost, new IP address, storage failure, system ready Edge storage: recording ongoing, storage disruption I/O: manual trigger, virtual input MQTT subscribe PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: average bitrate degradation, live stream open, tampering Video encoder: video connected	a.	<i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>
Event actions	Guard tours, upload of images or video clips, notification, overlay text, preset positions, recordings, SNMP trap messages, status LED, video clips MQTT publish	Environmental responsibility: axis.com/environmental-responsibility	