

# AXIS Q6010-E Network Camera

For 360° real-time monitoring and great detail

With four 5 MP sensors, AXIS Q6010-E provides a complete 360° overview with great image usability both day and night. Designed for operation with current AXIS Q60-E PTZ Network Cameras, it enables one-click PTZ control and autopilot for automatic PTZ tracking within the viewing areas. And, each sensor has exchangeable lenses with autofocus and positioning calibration for maximum flexibility and accurate configuration. AXIS Q6010-E uses the same bracket, power supply and network cable as the connected AXIS Q60-E PTZ Network Camera for cost-efficient installation. Furthermore, Zipstream with support for H.264/H.265 significantly lowers bandwidth and storage requirements without compromising image quality.

- > **360° camera with one-click PTZ control**
- > **4 x 5 MP sensors, total 20 MP resolution**
- > **Exchangeable and tiltable lenses**
- > **Requires a current AXIS Q60-E PTZ Network Camera**
- > **Autopilot included**



# AXIS Q6010-E Network Camera

<b>Models</b>	AXIS Q6010-E 50 Hz AXIS Q6010-E 60 Hz	Video: day-night mode, live stream open, tampering	
<b>Camera</b>		<b>Event actions</b>	
<b>Supported products</b>	AXIS Q6052-E PTZ Network Camera AXIS Q6054-E PTZ Network Camera AXIS Q6054-E Mk II PTZ Network Camera AXIS Q6054-E Mk III PTZ Network Camera AXIS Q6055-E PTZ Network Camera AXIS Q6074-E PTZ Network Camera AXIS Q6075-E PTZ Network Camera	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset Overlay text, day/night mode, Status LED, WDR mode	
<b>Image sensor</b>	4 x 5 MP progressive scan RGB CMOS 1/2.5"	<b>Data streaming</b>	
<b>Lens</b>	Autofocus lenses, Fixed iris, F2.0, Focal length: 2.8 mm Horizontal field of view: 360° Vertical field of view: 84°	<b>Built-in installation aids</b>	
<b>Day and night</b>	Automatically removable infrared-cut filter	Installation focus, lens selection, positioning calibration, ptz remote connection.	
<b>Minimum illumination</b>	Color: 0.4 lux at 50 IRE, F2.0 B/W: 0.03 lux at 50 IRE, F2.0	<b>General</b>	
<b>Shutter speed</b>	1/32500 to 1/20 s	<b>Casing</b>	IP66-, NEMA 4X- and IK10-rated Polycarbonate dome Aluminum casing
<b>Camera angle adjustment</b>	Pan, tilt and rotate	<b>Sustainability</b>	PVC free
<b>Pan/Tilt/Zoom</b>	One-click PTZ control	<b>Memory</b>	2048 MB RAM, 512 MB Flash
<b>Video</b>		<b>Power</b>	Power consumption without PTZ: PoE typical 9 W, max 22 W
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC), Main and High Profiles H.265 (MPEG-H Part 2/HEVC), Main Profile	<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX/1000BASE-T PoE RJ45 10BASE-T/100BASE-TX/1000BASE-T Q60-E port
<b>Resolution</b>	4 x 2592x1944 to 320x240 Default: 2592x1944	<b>Storage</b>	Support for SD/SDHC/SDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
<b>Frame rate</b>	Up to 20 fps (50/60 Hz) in all resolutions	<b>Operating conditions</b>	-50 °C to 50 °C (-58 °F to 122 °F) with AXIS Camera Heater Kit -40 °C to 50 °C (-40 °F to 122 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Start-up temperature: -40 °C (-40 °F) Humidity 10–100% RH (condensing)
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and H.265 Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth ABR/MBR H.264/H.265	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
<b>Image settings</b>	Resolution, compression, saturation, brightness, sharpness, contrast, white balance, exposure level, exposure mode, shutter & gain fine tuning of behavior at normal and low light, polygon privacy masks (maximum 8 per channel), WDR, dynamic text, image overlay	<b>Approvals</b>	EMC EAC, EN 55032 Class A, EN 55035, EN 50121-4, IEC 62236-4, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KN35 <b>Safety</b> IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 60950-22, CAN/CSA-C22.2 No. 60950-22 <b>Environment</b> IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9) <b>Network</b> NIST SP500-267
<b>Network</b>		<b>Dimensions</b>	ø 395 mm (15.6 in) Height: 201 mm (7.9 in)
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1x (EAP-TLS) <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware	<b>Weight</b>	4.5 kg (9.1 lb) excluding an AXIS Q60-E PTZ Network Camera
<b>Supported protocols</b>	IPv4, IPv6 USGv6, HTTP, HTTP/2, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>®</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, NTPIC, LLDP, MQTT, Syslog	<b>Included accessories</b>	Q60-E adapter, Bayonet screws, Installation guide, Windows <sup>®</sup> decoder 1-user license
<b>System integration</b>		<b>Optional accessories</b>	AXIS Lens M12 6 mm 5P (horizontal field of view: 56°, vertical field of view: 42°), AXIS Lens M12 12 mm 5P (horizontal field of view: 31°, vertical field of view: 23°), AXIS Lens M12 16 mm 5P (horizontal field of view: 20°, vertical field of view: 15°), AXIS T91 Mounting accessories, Axis Midspan 60 W 1-port, AXIS Camera Heater Power Supply For more accessories, see <a href="http://axis.com">axis.com</a>
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF <sup>®</sup> Profile G, ONVIF <sup>®</sup> Profile S, and ONVIF <sup>®</sup> Profile T, specification at <a href="http://onvif.org">onvif.org</a>	<b>Video management software</b>	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
<b>Analytics</b>	<b>Included</b> Autopilot, AXIS Video Motion Detection, AXIS Guard Suite including AXIS Motion Guard, AXIS Fence Guard, and AXIS Loitering Guard, active tampering alarm, edge storage events <b>Supported</b> Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>	<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese
<b>Event conditions</b>	Analytics, edge storage events, virtual inputs through API Device status: above operating temperature, above or below operating temperature, below operating temperature, fan failure, IP address removed, network lost, new IP address, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: manual trigger, virtual input PTZ: PTZ ready Scheduled and recurring: scheduled event	<b>Warranty</b>	5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([openssl.org](http://openssl.org)), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)