

AXIS V5938 PTZ Network Camera

Broadcast-quality 4K PTZ camera

AXIS V5938 combines excellent image quality with smooth PTZ control and broadcast-quality audio for professional webcasting. It's compatible with VISCA joysticks and VISCA over IP, making it easy to integrate with your existing AV installations. Offering enhanced security features such as signed firmware and secure boot, it ensures the integrity and authenticity of the firmware. Furthermore, Axis Zipstream with H.264 and H.265 significantly reduces bandwidth and storage requirements without compromising image quality.

- > **UHD 4K at 30 fps and 20x zoom**
- > **Broadcast-quality audio with XLR inputs**
- > **VISCA and VISCA over IP support**
- > **Camstreamer 3-month trial included**
- > **3G-SDI and HDMI outputs**



AXIS V5938 PTZ Network Camera

Camera		
Image sensor	Progressive scan RGB CMOS 1/2.5"	
Lens	4.4–88 mm, F2.0–3.8 Horizontal field of view: 70.2°–4.1° Vertical field of view: 39.5°–2.3° Autofocus, DC-iris control	Unbalanced external microphone Unbalanced line Line input impedance: >10 kOhm Maximum input level: 2.2 Vrms Bandwidth: 20 Hz - 20 kHz (±3 dB), may be limited by sample rate THD+N: < 0.03% Signal-to-Noise ratio: > 87 dB @ 0 dB gain, > 83 dB @ 30 dB gain
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	Color: 0.7 lux at 30 IRE F2.0 1 lux at 50 IRE F2.0 B/W: 0.06 lux at 30 IRE F2.0 0.1 lux at 50 IRE F2.0	3.5 mm output 3.5 mm unbalanced stereo output Output impedance: < 100 Ohm, short circuit proof Maximum output level: > 0.707 Vrms Bandwidth: 20 Hz - 20 kHz (±3 dB), may be limited by sample rate THD+N: < 0.03% @ 10 kOhm load Signal-to-Noise ratio: > 87 dB
Shutter speed	1/10000 s to 1 s	
Pan/Tilt/Zoom	Pan: ±170°, 0.2–100°/s Tilt: -20° - 90°, 0.2–90°/s Zoom: 20x Optical, 12x Digital, Total 240x 256 presets positions, Control queue, On-screen directional indicator, Adjustable zoom speed, PTZ response profiles	SDI output Bandwidth: 20 Hz - 20 kHz (±3 dB) THD+N: < 0.03% Signal-to-Noise ratio: > 87 dB
Video		HDMI output Bandwidth: 20 Hz - 20 kHz (±3 dB) THD+N: < 0.03% Signal-to-Noise ratio: > 87 dB
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	Network
Resolution	3840x2160 HDTV 2160p to 160x90 HDMI Output: 2160p@25/30 fps (50/60 Hz) 1080p@25/30/50/60 fps (50/60 Hz) 1080i@50/60 fps (50/60 Hz) 720p@50/60 fps (50/60 Hz) 480p@60 fps (60 Hz) SDI Output: 1080p@25/30/50/60 fps (50/60 Hz) 1080p@50/60 fps (50/60 Hz) dual stream 1080i@50/60 fps (50/60 Hz) 720p@50/60 fps (50/60 Hz)	Security Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot
Frame rate	Up to 30/25 fps (60/50 Hz) in 4K Up to 60/50 fps (60/50 Hz) in all other resolutions	Supported protocols IPv4/v6, HTTP, HTTP/2, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, SIP, LLDP, MQTT, Syslog, HDMI, 3G-SDI, VISCA
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 HDMI HD-SDI: SMPTE 292 3G-SDI: SMPTE 424, SMPTE 425 (3G-SDI mapping supports Level A / Level B dual link mapping)	System integration
Image settings	Saturation, brightness, sharpness, noise reduction, rotation: 0°, 180°, WDR – dynamic contrast, white balance, day/night threshold, exposure zones, backlight compensation, defogging, highlight compensation, electronic image stabilization	Application Programming Interface Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G and ONVIF [®] Profile S, specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.
Audio		Event conditions Analytics, external input, edge storage events, virtual inputs through API Audio: audio detection Call: state, state change Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address removed, network lost, new IP address, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: digital input, manual trigger, virtual input PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: average bitrate degradation, live stream open
Audio streaming	Two-way, stereo HD-SDI: SMPTE ST 299-1 3G-SDI: SMPTE ST 299-2	Event actions Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset Overlay text, external output activation, play audio clip, zoom preset, day/night mode, make call
Audio encoding	SDI: AES3 24 bit, 48 kHz HDMI: LPCM Network: AAC LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 48 kHz, Configurable bit rate	Data streaming Event data
XLR input	2 balanced inputs (left/right) Microphone phantom power 48 V Balanced external microphone Balanced line level Line input impedance: >10 kOhm Maximum input level: 4.4 Vrms Bandwidth: 20 Hz - 20 kHz (±3 dB), may be limited by sample rate THD+N: < 0.03% Signal-to-Noise ratio: > 85 dB @ 0 dB gain, > 78 dB @ 30 dB gain	Built-in installation aids Pixel counter, leveling guide
3.5 mm input	Microphone Power 5 V via 2.2 kOhm	Analytics
		Applications Included AXIS Video Motion Detection, AXIS PTZ Autotracking Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/aca

General	
Casing	ASA plastic cover Color: White NCS S 1002-B
Memory	2 GB RAM, 512 MB Flash
Power	11–13 V DC (12 V power supply included), typical 17.5 W, max 20 W
Connectors	RJ45 10BASE-T/100BASE-TX/1000BASE-T Terminal block for 1 alarm input and 1 output 3.5 mm stereo mic/line in, 3.5 mm stereo line out XLR-3 (left + right) mic/line in (with 48 V phantom power) HDMI Type A, BNC for SDI DC input RS232 serial connector for VISCA
Storage	Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity 10–85% RH (non-condensing)
Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F) Humidity 5 – 95% RH (non-condensing)
Approvals	EMC EN 55032 Class A, EN 55024, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, CISPR 24, CISPR 35, KC KN32 Class A, KC KN35
	Safety IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, KC-Mark
	Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78
	Network NIST SP500-267
Dimensions	Height: 180 mm (7.1 in) ø 136 mm (5.4 in)
Weight	1.5 kg (3.3 lb)
Included accessories	Power supply, wall/ceiling mount, terminal connector for I/O, installation guide, Windows® decoder user license, Camstreamer 3-month trial
Optional accessories	AXIS T8310 Video Surveillance Control Board AXIS VISCA Cable For more accessories, see axis.com
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Warranty	5-year warranty, see axis.com/warranty
	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>
	Environmental responsibility: axis.com/environmental-responsibility